



A P P R O V A L S ®

Certificate of Suitability

Certificate No.: SAA231133

Certificate Holder: Letaron Electronic Co., Ltd.
No.253, Junma Road,
Hengli Town, 523460 Dongguan City,
Guangdong Province
P.R. China

Regulatory Definition: Non-Prescribed

Product Description: LED Driver (Built-in, Constant Voltage, SELV)

Standard/s: AS/NZS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: All approved models of LED drivers must comply with
Standard requirements of end product when installed.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA231133

Initial Issue Date: 1 September 2023

Expiry Date: 1 September 2028

R.A. Hill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 01-09-23 231133
Page 1 of 2



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
AED40-12VLSTB-IP44	LETARON	Input: 220-240V~ 50/60Hz Output: 12Vdc, Max 3.33A, 40W Max: 15V (no load) ta:40°C, tc:80°C, Thermal protection 110, IP44, SELV, Symbol for Built-in electronic controlgear with Double/Reinforced insulation
AED40-24VLSTB-IP44	LETARON	Input: 220-240V~ 50/60Hz Output: 24Vdc, Max 1.67A, 40W Max: 28V (no load) ta:40°C, tc:80°C, Thermal protection 110, IP44, SELV, Symbol for Built-in electronic controlgear with Double/Reinforced insulation
AED48-12VLSTB-IP44	LETARON	Input: 220-240V~ 50/60Hz Output: 12Vdc, Max 4A, 48W Max: 15V (no load) ta:40°C, tc:80°C, Thermal protection 110, IP44, SELV, Symbol for Built-in electronic controlgear with Double/Reinforced insulation
AED48-24VLSTB-IP44	LETARON	Input: 220-240V~ 50/60Hz Output: 24Vdc, Max 2A, 48W Max: 28V (no load) ta:40°C, tc:80°C, Thermal protection 110, IP44, SELV, Symbol for Built-in electronic controlgear with Double/Reinforced insulation

R. A. Hill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 01-09-23 231133
Page 2 of 2