

JETFLUSH

Sentinel JetFlush Rapid



Technical Specification

- Tank capacity: 39L
- Dimensions: (height) 690mm x (width) 390mm x (depth) 440mm
- Weight: 17kg (empty), 56kg (full)
- Flow rate: 90L/min
- Power requirement: 230V, 50Hz single phase motor, Nominal rating: 3.0amp
- Pressure Rating: Recirculating - 10psi, against closed valve - 22psi
- Maximum temperature: 75°C
- Instantaneous flow reversal
- Self priming



Application

The Sentinel JetFlush Rapid is used in plumbing, heating & cooling systems to clean, sterilize or treat water and is installed mostly in plant rooms.

Warranty

[Download the latest warranty statement](#)

Features

The Sentinel JetFlush Rapid unit is designed to be used in conjunction with the Sentinel range of chemical cleaning products for the safe and easy removal of the sludge and debris from central heating systems.

High flow rate and reversible flow. Enables rapid and effective removal of debris, quickly helping to restore optimum system efficiency.

Complete with easy-to-use hoses and fittings. Allows unit to be easily and quickly connected anywhere on the system.

Lightweight and compact with ergonomic design. Easy to handle and operate: ideal for small properties.

Integral fresh water flush facility. Allows direct flush of all debris to waste and not returned to the system.